

Fine Tuning the **DryFireMag**® for PSA MICRO Dagger

(Changing trigger-pull-weight, and the timing of the trigger-break for your particular firearm)

The easiest way (and the recommended way) to adjust the trigger pull-weight of your **DryFireMag** for the **PSA MICRO Dagger** is by swapping the stock spring for the lighter spring included in the wrench bag. To **lessen** the **pull-weight**, simply exchange the included spring (in your wrench bag) with the stock spring at the top of the mag. A "Spring Kit" is not recommended for the DryFireMag for **PSA MICRO Dagger** due to a limited, optimal functionality with heavier or lighter springs than the ones included with the purchase.

(Always wear safety glasses when inserting or extracting springs)

Insert tip of small flat-head here.
Compress the spring, and pull up.



NOTE: Wear safety glasses when changing springs!

To **extract the stock spring**, insert a small flat-head screwdriver between the lever and first coil, compress the spring slightly, pull the spring up and out. To seat the replacement spring, set one end of the coil over the lever's spring retainer knob, compress the spring slightly, then drop the other end into the spring pocket. Manually operate the lever a few times to insure that the spring got seated properly.

ADJUSTING TRIGGER-BREAK-POINT TIMING (Point of release/simulated firing pin activation)

The timing of the DryFireMag's Trigger-Break-Point (breaking through the "wall", or the timing of the "click", as it is often referred to by customers) is adjusted through the top/rear port on this particular mag, using the provided #10 Allen wrench. Turning the screw clockwise will shorten the pre-travel. Turning counter-clockwise will delay the break. Incrementally making 1/8 turn adjustments is safest, and best.

It's a good idea to record the adjustments and check your results after each one. Exceeding 1 full turn either direction should be avoided. Also, excessive in & out of the Allen screw can cause timing instability if the self-tapping threads become worn due to wrench misalignment or excessive adjustment. (Note: Typically, advancing the action (reducing pre-travel) will cause the trigger pull-weight to drop slightly when measured on a spring scale.)

*Specifically pictured is the **SMART DryFireMag** for the **PSA MICRO Dagger**. Tuning for Trigger-Break & Pull-Weight is the same whether a **SMART** or **Standard DryFireMag**.*

Interchangeable Coil Spring for changing the Pull-Weight

Set Screw for adjusting the Trigger-Break-Point

DryFireMag for the PSA MICRO Dagger

NOTE: Though similar in appearance to the DryFireMag for the Glock 43X, it is **NOT** the same mag internally, and has different limitations.

