

Fine Tuning your DryFireMag® for the Springfield XD

Your DryFireMag® has been tested and adjusted to the standard trigger pull-weight of 5 - 5^{1/2} lbs. An extra coil spring has been included with your purchase (bagged with the adjustment Allen wrench) as a way to easily increase this weight by a modest amount.

Note: Even though the mag for the **XD**, and the mag for the **XDM** look very similar; they are "configured" differently to accommodate the differences in the triggers.

(Always wear safety glasses when inserting or extracting springs).

To exchange the spring, Insert the tip of a small flat-head screw-driver between the first two coils of the stock spring nearest the lever, compress, and pull up and out. To replace with the heavier spring, place one end of the spring on the lever post first, compress the spring against the post, then force the other end into the spring-retainer-pocket just opposite the post. Manually actuate the lever a few times to make sure that the spring is properly seated.

Adjusting the amount of pre-travel, or the point of the simulated release of the firing pin:



1. Locate the #10 Allen wrench and the top hole on the FRONT of the magazine.
2. **To shorten the trigger pre-travel** (cause an earlier break). turn the set screw **clockwise** 1/8 turn (45°). Reinsert the DryFireMag® and test. If a shorter pre-travel is still desired, repeat adjustment and retest. **Do not turn this adjustment CW more than 1 3/4 total turns.**
3. **To lengthen the trigger pre-travel** (cause a later break), turn the set screw **counter-clockwise** 1/8 of a turn. Reinsert the DryFireMag® and test. If a longer pre-travel is still desired, repeat adjustment and retest. **Do not turn CCW more than 1/4 total turns.**